

Display diagonal	48.50 Inches (1232.00mm)
Active Display Area	1073.80 x 604.00 mm
Resolution	3.840 x 2.160px @ 60 Hz / 16:9
Panel Type	IPS Hard-Coating (3H), Anti-Glare Treatment
Brightness	450 cd/m2
Contrast	1.200:1
Viewing Angle	178° H/V
Colors	10 bit, 1.07Billion colors
Color Gamut	NTSC 72%, sRGB2 99%
Anti-Glare (Haze)	25%
Orientation	Landscape / Portrait
Connections	1x USB, 1x RJ out, 1x RJ45c, 1x RS232c, 1x Micro SD Card, 1x USB Type C (Power Supply)
Operation Time	24 / 7
Operating Conditions	Temperature 0°C to 50°C / Humidity 10-80%
Storage Conditions	Temperature -20°C to 50°C / Humidity 5-90%
Delivered Contents	Power Adapter, Mounting Plate
Integrated Computer	BrightSign 4K Player integrated (3840x2160px) VIDEO H.265/H.264 .MOV, .MP4, .MKV, .TS IMAGE BMP, JPEG, PNG WI-FI/Bluetooth Module (Optional)
BrightSign Supported	BrightAuthor®, BrightBeacon, BrightWall, Zones, Mosaic Mode, IP Streaming, Live Feeds, Tagging, BrightSign App (iOS), Geo-Fencing (requires USB dongle), Sign Preview, Remote Snapshot, Networking, B-eploy
Dimensions	1106.20 x 636.40 x 35 mm (Even Thickness) / Bezel 15.2 mm (Even Bezel)
VESA	300 x 300 mm
Weight	14 Kg (Net); 18 Kg (Gross)
Power Consumption	Operation 100W / Standby 0.5W (24V/6A, Source 100-240V 60W)
Certifications	CE
Warranty	2 Years Parts & Labor